



ENFRIADORES



INFORMACION TECNICA ENFRIADORES

MODELO	Capacidad Frigorifica		Pot. Eléctrica	Caudal líquido	Conexión	DIMENSIONES		
	Kcal/h	Kw/h.	Total Kw/h	Refrigerado m ³ /h	Ø BSP	Largo	Ancho	Alto
ISR 14	11.000	13	5	4	1" BSP	1.100	850	1.350
ISR 18	17.000	19	7	6	1" BSP	1.100	850	1.350
ISR 24	21.000	24	10	7	1 1/4" BSP	1.450	900	1.500
ISR 33	29.000	34	14	10	1 1/4" BSP	1.450	900	1.500
ISR 50	44.000	51	16	15	1 1/2" BSP	1.850	900	1.650
ISR 65	58.000	67	19	20	2" BSP	2.200	1.000	2.000
ISR 80	76.000	87	25	25	1" BSP	2.200	1.000	2.000
ISR 105	90.000	105	30	30	2" BSP	2.200	1.000	2.000
ISR 105 DC	88.000	102	30	30	2 1/2" BSP	2.200	1.000	2.000
ISR 125 DC	116.000	134	38	35	2 1/2" BSP	2.200	1.000	2.000
ISR 160 DC	152.000	174	48	50	3" Bridas	2.200	2.000	2.000
ISR 200 DC	180.000	210	56	60	3" Bridas	2.200	2.000	2.000
ISR 205 TC	174.000	201	61	60	3" Bridas	3.400	2.000	2.200
ISR 250 TC	228.000	260	72	80	3" Bridas	3.400	2.000	2.300
ISR 380 DC	304.000	348	95	100	4" Bridas	3.500	2.000	2.300
ISR 400 DC	360.000	420	110	120	5" Bridas	3.500	2.000	2.300

Temperatura de Agua Refrigerada 10 °C - Temperatura Aire Ambiente 25 °C

Datos sujetos a cambios sin previo aviso

